

НАСОСНО-КОМПРЕССОРНЫЕ ТРУБЫ стандарт API 5 CT

	Удельный вес, кг/м		Наружный диаметр		Толщина стенки		Тип высадки			
	Гладкая (NU)	С высадкой (EUE)	мм	дюйм	мм	дюйм	J55	N80	L80	P110
2 3/8"	6.85	6.99	60.32	2.375	4.83	0.190	PNU	PNU	PNU	PNU
	8.63	8.85	60.32	2.375	6.45	0.254	-	PNU	-	PNU
	9.82	-	60.32	2.375	7.49	0.295	-	-	-	-
	10.94	11.09	60.32	2.375	8.53	0.336	-	-	-	-
2 7/8"	9.52	9.67	73.02	2.875	5.51	0.217	PNU	PNU	PNU	PNU
	11.61	11.76	73.02	2.875	7.01	0.276	-	PNU	PNU	PNU
	12.80	12.95	73.02	2.875	7.82	0.308	-	PNU	PNU	PNU
	13.91	14.06	73.02	2.875	8.64	0.340	-	-	PU	-
	15.63	-	73.02	2.875	9.96	0.392	-	-	P	-
	17.11	-	73.02	2.875	11.18	0.440	-	-	P	-
3 1/2"	11.46	-	88.90	3.500	5.49	0.216	PN	PN	PN	-
	13.69	13.84	88.90	3.500	6.45	0.254	PNU	PNU	PNU	PNU
	15.18	-	88.90	3.500	7.34	0.289	PN	PN	PN	-
	18.90	19.27	88.90	3.500	9.52	0.375	-	PNU	PNU	PNU
	21.28	-	88.90	3.500	10.92	0.430	-	-	P	-
	23.07	-	88.90	3.500	12.09	0.476	-	-	P	-
	25.30	-	88.90	3.500	13.46	0.530	-	-	P	-
4"	14.14	-	101.60	4.000	5.74	0.226	PN	PN	PN	-
	-	16.37	101.60	4.000	6.65	0.262	PU	PU	PU	-
	19.64	-	101.60	4.000	8.38	0.330	-	-	P	-
	23.96	-	101.60	4.000	10.54	0.415	-	-	P	-
	28.13	-	101.60	4.000	12.70	0.500	-	-	P	-
	33.04	-	101.60	4.000	15.49	0.610	-	-	P	-
4 1/2"	18.75	18.97	114.30	4.500	6.88	0.271	PNU	PNU	PNU	-
	22.62	-	114.30	4.500	8.56	0.337	PNU	PNU	PNU	-
	25.30	-	114.30	4.500	9.65	0.380	PNU	PNU	PNU	-
	28.13	-	114.30	4.500	10.92	0.430	-	-	P	-
	32.00	-	114.30	4.500	12.70	0.500	-	-	P	-
	35.27	-	114.30	4.500	14.22	0.560	-	-	P	-
	38.84	-	114.30	4.500	16.00	0.630	-	-	P	-

P – без резьбы и высадки

N – без высадки с гладкими концами

U – с резьбой и высадкой